

KDC100 Laser Barcode Data Collector

A New Wave in Auto-ID

The KDC100 enables diverse mobile Auto-Identification applications for collecting and storing barcode data.

A built-in display eliminates blind erroneous data collection and enables interactive data collection processes.

An easy-to-replace rechargeable battery that can recharge from any USB port allows more than 5,000,000 barcode scans. With 4MB of on-board memory that stores over 100,000 product records, memory shortages are no longer a concern.

All KDC® products come with FREE KTSync® software and SDK. KTSync® includes keyboard wedging, application generation, DB look up, and inventory management features. SDK provides technical support from our top engineers and development staff.



ADVANCED FEATURES

- Ultra Compact & Lightweight
- Bright 1" OLED Display
- Rechargeable Li-Poly Battery
- Built-in & swing-out USB Port
- Stores 100,000+ Product Records
- KTSync® with Keyboard Wedging, Application Generation, DB Look up, and Inventory Management features



BlackBerry



Windows



Mac

Solutions

- Retail
- Transportation
- Field Services
- Warehouse
- Healthcare
- Hospitality
- Event Technology



KDC100 Specifications

Hardware Specifications

Physical Characteristics

Size : 35 mm x 62 mm x 15 mm

(1.37" x 2.44" x 0.59")

Weight : 1.34 oz. (38 grams)

Electrical Characteristics

Battery : Lithium-Polymer (3.7V DC, 190mAh)

Charging : USB connector

Typical Operating Current : 100mAh@3.3V

Scanning Performance

Scan Rate : 100 scans/sec

User Environment

Drop Spec : 4 feet (1.22m) with a rubber case

Operating : 32°F (0°C) ~ 113°F (45°C)

Storage : -4°F (-20°C) ~ 113°F (45°C)

Humidity : 5% ~ 85% (noncondensing)

Interfaces

Two USB to Serial interfaces

- Swing-out USB Type A connector
- Built-in ultra mini USB port

Functionality

Memory Flash ROM : 256KB Program, 4MB User Data

Memory RAM : 64KB

Microprocessor : ARM7, 32 bits

Real-time Clock : Quartz RTC for timestamp

For more information, contact:

KOAMTAC, Inc.

116 Village Blvd. Suite 305
Princeton, NJ 08540, USA

Tel +1-609-256-4700

Fax +1-609-228-4373

E-mail info@KOAMTAC.com

www.koamtac.com

Symbologies

EAN, UPC, Code 39, Code 93, Code 128, Codabar, Interleaved 2 of 5, GS1-128, Code 3 of 5

Wedging & Synchronization

- Store to a file or transfer to the application
- Keyboard wedge function
- Add-on prefixes and suffixes
- Barcode option selection

Application Generation

- SDK for PC, Smartphone, and Tablet application
- Application generation tool
- Database lookup feature
- Inventory management feature

Regulatory Conformance

Laser Safety - IEC / CDRH Class II

EMC - CE, FCC, KCC

Models

KDC100, KDC100M

Package Contents



1 KDC100
Data Collector



1 Protective
Boot



1 Lanyard



1 USB Cable

